



Product Specification

Model Name	LM035NV08NS
Description	Standard LCD Module 3.5" VGA 480x(RGB)x640 Dots
Date	2018/09/03
Version	1.0

- Preliminary Specification
- Final Product Specification

Prepared by	Checked by	Approved by
SXY 2018/09/03	SXY 2018/09/03	LX 2018/09/03

For Customer Approval

Approved By	Comment



深圳市美显实业有限公司 LCD Mall Limited

Table of Contents

1. Record of Revision	3
2. General Specifications	4
3. Input/OutputTerminals.....	5
4. Absolute Maximum Rating	5
5. Electrical Characteristics	6
6. Interface Timing	8
7. Optical Characteristics	10
8. Environmental / Reliability Tests.....	13
9. Mechanical Drawing	14
10. Packing.....	15
11. TFT-LCD Module Inspection Criteria	16
12. Precautions for Use of LCD modules.....	21



1. Record of Revision

Rev	Issued Date	Description	Editor
1.0	2018/09/03	First Release.	SXY



2. General Specifications

	Feature	Spec
Characteristics	Size	3.5 inch
	Resolution	480(horizontal)*640(Vertical)
	Interface	18-BIT RGB-SPI
	Pixel pitch (mm)	0.1116*0.1116
	Pixel Configuration	R.G.B.-Stripe
	LCD Driver IC	HX8363-A
	CTP Driver IC	TBD
	Viewing Direction	ALL
Mechanical	LCM (W x H x D) (mm)	64.0*85.0*3.0
	Active Area(mm)	53.57*71.42
	With /Without TSP	Without TSP
	Weight (g)	TBD
	LED Numbers	6 LEDs

Note 1: Requirements on Environmental Protection: RoHs

Note 2: LCM weight tolerance: +/- 5%



3. Input/Output Terminals

LCD PIN-MAP

No.	Symbol	Description
1	DE	Data input enable
2~4	GND	Power Ground
5	NC	No connect
6~11	R0~R5	Red data
12~17	G0~G5	Green data
18~23	B0~B5	Blue data
24	SCL	Serial clock input
25	SDA	Data output pin in serial interface
26	/CS	Chip select pin
27	DOTCLK	Dot-clock signal and oscillator source
28	/RESET	System reset pin
29	HSYNC	Horizontal sync signal
3	VSNC	Vertical sync signal
31~32	VCC	Power supply
33	GND	Power Ground
34	LED_A	Anode of LED backlight
35	LED_K	Cathode of LED backlight
36	GND	Power Ground
37~40	NC	No connect

4. Absolute Maximum Rating

Item	Symbol	MIN	MAX	Unit
Supply voltage for analog	Vcc	-0.3	4.5	V
Supply voltage for logic	IOVCC	-0.3	4.5	V
Supply current (One LED)	I _{LED}		30	mA
Operating temperature	T _{OP}	-20	+70	°C
Storage temperature	T _{ST}	-30	+80	°C

Note: The absolute maximum rating values of this product are not allowed to be exceeded at any times.

Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed



5. Electrical Characteristics

5.1 Input Power


Item	Symbol	Min	Typ	Max	Unit	Applicable terminal
Supply Voltage for Analog	VCC	2.5	2.8	3.3	V	
Supply Voltage for Logic	VCC	2.5	2.8	3.3	V	
Input Voltage	V _{IL}	0	-	0.3VCC	V	
	V _{IH}	0.7VCC	-	VCC		
Input leakage Current	I _{LKG}	-	-	-	uA	

5.2 Backlight Driving Conditions

Item	Symbol	Value			Unit	Remark
		Min	Typ	Max		
Voltage for LED Backlight	V _F	16.8	19.2	20.4	V	I _L =20mA
Current for LED Backlight	I _L		20		mA	
Power Consumption	P		0.384		W	
LED Life Time		30,000	50,000		Hr	Note

Note: Brightness to be decreased to 50% of the initial value at ambient temperature TA=25°C

5.3 Block Diagram



6. Interface Timing

6.1 RGB Interface Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Vertical cycle	VP	-	806	-	810	Line
Vertical low pulse width	VS	-	2	-	4	Line
Vertical front porch	VFP	-	2	-	4	Line
Vertical back porch	VBP	-	2	-	4	Line
Vertical data start point	-	VS+VBP	4	-	8	Line
Vertical blanking period	VBL	VS+VBP+VFP	6	-	10	Line
Vertical active area	-	VDISP	-	800	-	Line
Vertical Refresh rate	VRR	-	50	-	70	Hz


Note: (1) Signal rise and fall times are equal to or less than 20 ns.

(2) Input signals are measured by $0.50 \times VDD1$ for low state and $0.70 \times VDD1$ for high state.

(3) Data lines can be set to "High" or "Low" during blanking time – Don't care.

(4) VRR must keep from 50Hz to 70Hz when adjust other items

Horizontal Timings for RGB I/F



Item	Symbol	Condition	Min.	Typ.	Max.	Unit
HS cycle	HP	Note ⁽³⁾	504	-	568	DCK
HS low pulse width	HS	-	5	-	78	DCK
Horizontal back porch	HBP	-	5	-	78	DCK
Horizontal front porch	HFP	-	5	-	78	DCK
Horizontal data start point	-	HS+HBP	19	-	83	DCK
			700	-	-	ns
Horizontal blanking period	HBLK	HS+HBP+HFP	24	-	88	DCK
Horizontal active area	HDISP	-	-	480	-	DCK
Pixel clock frequency When RGB I/F is running	DCK	VRR = Min. 50Hz - Max. 70Hz	21.6	-	34.3	MHz
			29.1	-	46.2	ns

Note: (1) Signal rise and fall times are equal to or less than 20 ns.

(2) Input signals are measured by 0.30 x VDD1 for low state and 0.70 x VDD1 for high state.

(3) HP is multiples of eight DCK.

(4) Data lines can be set to "High" or "Low" during blanking time – Don't care.

(5) VRR must keep from 50Hz to 70Hz when adjust other items.

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
HS cycle	HP	Note ⁽³⁾	504	-	568	DCK
HS low pulse width	HS	-	5	-	78	DCK
Horizontal back porch	HBP	-	5	-	78	DCK
Horizontal front porch	HFP	-	5	-	78	DCK
Horizontal data start point	-	HS+HBP	19	-	83	DCK
			700	-	-	ns
Horizontal blanking period	HBLK	HS+HBP+HFP	24	-	88	DCK
Horizontal active area	HDISP	-	-	480	-	DCK
Pixel clock frequency When RGB I/F is running	DCK	VRR = Min. 50Hz - Max. 70Hz	20.3	-	32.2	MHz
			31	-	49.2	ns

Note: (1) Signal rise and fall times are equal to or less than 20 ns.


(2) Input signals are measured by 0.30 x VDD1 for low state and 0.70 x VDD1 for high state.

(3) HP is multiples of eight DCK.

(4) Data lines can be set to "High" or "Low" during blanking time – Don't care.

(5) VRR must keep from 50Hz to 70Hz when adjust other items.

General Timings for RGB I/F



7. Optical Characteristics

ITEM	SYMBOL	CONDITIONS	SPECIFICATIONS			UNIT	NOTE
			MIN	TYP	MAX		
Luminance	L	IL=20mA	120	150	180	Cd/m ²	
Contrast Ratio	CR	$\theta=0^\circ$		300			
Response Time	T _{ON}	25°C		30	50	ms	
	T _{OFF}						
CIE Color Coordinate	Red	X _R	0.474	0.514	0.554		
		Y _R	0.301	0.341	0.381		
	Green	X _G	0.293	0.334	0.374		
		Y _G	0.503	0.543	0.583		
	Blue	X _B	0.114	0.154	0.194		
		Y _B	0.089	0.129	0.169		
	White	X _W	0.258	0.298	0.338		
		Y _W	0.305	0.345	0.385		
Viewing Angle	Hor	θ_{x+}	60	80		Degree	Gray Scale inversion
		θ_{x-}	60	80			
	Ver	θ_{y+}	60	80			
		θ_{y-}	60	80			
Uniformity	Un		80			%	

Note1. Definition of contrast ratio

Contrast ratio(Cr) is defined mathematically by the following formula. For more information see FIG.2.

$$\text{Contrast ratio} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

For contrast ratio, Surface Luminance, Luminance uniformity and CIE,the testing data is base on TOPCON's BM-5 or BM-7 photo detector or compatible.

Note2. Definition of surface luminance.

Surface luminance is the luminance with all pixels displaying white. For more information see FIG.2.

Lv = Average Surface Luminance with all white pixels(P1,P2,P3,,Pn)

Note3. Definition of luminance uniformity

The luminance uniformity in surface luminance is determined by measuring luminance at each test position 1 through n, and then dividing the maximum luminance of n points luminance by minimum luminance of n points luminance.For more information see FIG.2.

$$YU = \frac{\text{Minimum surface luminance with all white pixels (P1,P2,P3,.....,Pn)}}{\text{Maximum surface luminance with all white pixels (P1,P2,P3,.....,Pn)}}$$

Note4. Definition of response time

The response time is defined as the LCD optical switching time interval between “White” state and “Black”state. Rise time (Tr) is the time between photo detector output intensity changed from 90% to 10%. And fall time (Tf) is the time between photo detector output intensity changed from 10% to 90%.

For additional information see FIG1.

Note5. Definition of color chromaticity (CIE1931)

CIE (x,y) chromaticity, The x,y value is determined by screen active area center position P5. For more information see FIG.2.

Note6. Definition of viewing angle

Viewing angle is the angle at which the contrast ratio is greater than 10. Angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG.3.

For viewing angle and response time testing, the testing data is base on Autronic-Melchers’s ConoScope or DMS series Instruments or compatible.

FIG.1. The definition of response Time




FIG.2. Measuring method for contrast ratio, surface luminance,

luminance uniformity, CIE (x,y) chromaticity

Size : S≤5”(see Figure a) A : 5 mm B : 5 mm

H,V : Active area

Light spot size $\phi=5\text{mm}$ (BM-5) or $\phi=7.7\text{mm}$ (BM-7) 50cm distance or compatible distance from the LCD surface to detector lens.

test spot position : see Figure a.

measurement instrument : TOPCON’s luminance meter BM-5 or BM-7 or compatible (see Figure c).




Figure a

Size : 5" < S ≤ 12.3" (see Figure b) H,V : Active area

Light spot size $\phi=5\text{mm}$ (BM-5) or $\phi=7.7\text{mm}$ (BM-7) 50cm distance or compatible distance from the LCD surface to detector lens.

test spot position : see Figure b.

measurement instrument : TOPCON's luminance meter BM-5 or BM-7 or compatible (see Figure c).






FIG.3.The definition of viewing angle




8. Environmental / Reliability Tests

No	Test Item	Condition	Remarks
1	High Temperature Operation	Ts= +70°C, 240hrs	Note 1 IEC60068-2-2, GB2423.2-89
2	Low Temperature Operation	Ta= -20°C, 240hrs	Note 2 IEC60068-2-1 GB2423.1-89
3	High Temperature Storage	Ta= +80°C, 240hrs	IEC60068-2-2 GB2423.2-89
4	Low Temperature Storage	Ta= -30°C, 240hrs	IEC60068-2-1 GB/T2423.1-89
5	High Temperature & Humidity Storage	Ta= +60°C, 90% RH max, 240 hours	IEC60068-2-3 GB/T2423.3-2006
6	Thermal Shock (Non-operation)	-20°C 30 min ~ +60°C 30 min Change time: 5min, 20 Cycle	Start with cold temperature, end with high temperature IEC60068-2-14, GB2423.22-87
7	Electro Static Discharge (Operation)	C=150pF, R=330 Ω, 5 points/panel Air:±8KV, 5 times; Contact: ±4KV, 5 times; (Environment: 15°C ~ 35°C, 30% ~ 60%, 86Kpa ~ 106Kpa)	IEC61000-4-2 GB/T17626.2-1998
8	Vibration (Non-operation)	Frequency range: 10~55Hz, Stroke: 1mm Sweep: 10Hz~55Hz~10Hz 2 hours for each direction of X.Y.Z. (package condition)	IEC60068-2-6 GB/T2423.5-1995
9	Shock (Non-operation)	60G 6ms, ± X, ±Y, ± Z 3 times for each direction	IEC60068-2-27 GB/T2423.5-1995
10	Package Drop Test	Height: 80 cm, 1 corner, 3 edges, 6 surfaces	IEC60068-2-32 GB/T2423.8-1995


- Note: 1. Ts is the temperature of panel's surface.
2. Ta is the ambient temperature of sample.
3. The size of sample is 5pcs.

9. Mechanical Drawing



10. Packing

Packing Method



11. TFT-LCD Module Inspection Criteria

11.1 Scope

The incoming inspection standards shall be applied to TFT –LCD Modules (hereinafter Called "Modules") that supplied by LCD Mall Limited.

11.2 Incoming Inspection

The customer shall inspect the modules within twenty calendar days of the delivery date (the inspection period) at its own cost. The result of the inspection (acceptance or rejection) shall be recorded in writing, and a copy of this writing will be promptly sent to The seller, If the results of the inspecting from buyer does not send to the seller within twenty Calendar days of the delivery date. The modules shall be regards as acceptance.

Should the customer fail to notify the seller within the inspection period, the buyers Right to reject the modules shall be lapsed and the modules shall be deemed to have Been accepted by the buyer

11.3 Inspection Sampling

- 3.1. Lot size: Quantity per shipment lot per model
 - 3.2. Sampling type: Normal inspection, Single sampling
 - 3.3. Inspection level: II
 - 3.4. Sampling table: MIL-STD-105E
 - 3.5. Acceptable quality level (AQL)
- Major defect: AQL=0.65 Minor defect: AQL=1.00

11.4 Inspection Conditions

4.1 Ambient conditions:


- a. Temperature: Room temperature $25\pm 5^{\circ}\text{C}$
- b. Humidity: $(60\pm 10)\% \text{RH}$
- c. Illumination: Single fluorescent lamp non-directive (300 to 700 Lux)

4.2 Viewing distance

The distance between the LCD and the inspector's eyes shall be at least $35\pm 5 \text{ cm}$.

4.3 Viewing Angle

U/D: $45^{\circ}/45^{\circ}$, L/R:



$45^{\circ}/45^{\circ}$


11.5 Inspection Criteria





Defects are classified as major defects and minor defects according to the degree of Defectiveness defined herein.

11.5.1 Major defect


Item No	Items to be inspected	Inspection Standard
5.1.1	All functional defects	1) No display 2) Display abnormally 3) Short circuit 4) line defect
5.1.2	Missing	Missing function component
5.1.3	Crack	Glass Crack

11.5.2 Minor defect

Item No	Items to be inspected	Inspection standard	
5.2.1	Spot Defect Including Black spot White spot Pinhole Foreign particle Polarizer dirt	For dark/white spot is defined $\phi = (x+y) / 2$ 	
		Size ϕ (mm)	Acceptable Quantity
		$\phi \leq 0.2$	Ignore
		$0.2 < \phi \leq 0.5$	3
		$0.5 < \phi$	Not allowed

5.2.2	Line Defect Including Black line White line Scratch	Define: 		
		Width(mm) Length(mm)		Acceptable Quantity
		W≤0.05		Ignore
		0.05 < W≤0.1 L≤2.5		3
		0.1 < W, or L>2.5		Not allowed
5.2.3	Polarizer Dent/Bubble	Sizeφ(mm)		Acceptable Quantity
		φ≤0.2		Ignore
		0.2 < φ≤0.3		2
		0.3 < φ≤0.5		1
		0.5 < φ		Not allowed
		Total QTY		3
5.2.4	Electrical Dot Defect	Bright and Black dot define:  and 		
				
		Two Adjacent Dot		
		Inspection pattern: Full white、 Full black、 Red、 green and blue screens		
		Item		Acceptable Quantity
		I	O	Note
Black dot defect		2		

		Bright dot defect	1	(5mm≤Distance)
		Two Adjacent Dot	1	
		There or more Adjacent Dot	Not allowed	
		Total Dot	2	
5.2.5	Glass defect	<p>1. Corner Fragment:</p>		
		Size(mm)	Acceptable Quantity	
		X≤3mm Y≤1mm Z≤T	Ignore T: Glass thickness X: Length Y: Width Z: thickness	
		<p>2. Side Fragment:</p>		
		Size(mm)	Acceptable Quantity	
X≤5.0mm Y ≤1mm Z≤T	T: Glass thickness X: Length Y: Width Z: thickness			





I area & O area

- Note:
- 1). Dot defect is defined as the defective area of the dot area is larger than 50% of the dot area.
 - 2). The distance between two bright dot defects (red, green, blue, and white) should be larger than 15mm.
 - 3). The distance between black dot defects or black and bright dot defects should be more than 5mm apart.
 - 4). Polarizer bubble is defined as the bubble appears on active display area. The defect of polarizer bubble shall be ignored if the polarizer bubble appears on the outside of active display area.

11.6 Mechanics specification

As for the outside dimension, weight of the modules, please refer to product specification
For more details



12. Precautions for Use of LCD modules

12.1 Handling Precautions

12.1.1. The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

12.1.2. If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

12.1.3. Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

12.1.4. The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

12.1.5. If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

Isopropyl alcohol & Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following: Water & Ketene & Aromatic solvents

12.1.6. Do not attempt to disassemble the LCD Module.

12.1.7. If the logic circuit power is off, do not apply the input signals.

12.1.8. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

12.1.8.1. Be sure to ground the body when handling the LCD Modules.

12.1.8.2. Tools required for assembly, such as soldering irons, must be properly ground.

12.1.8.3. To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

12.1.8.4. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

12.2 Storage Precautions

12.2.1. When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

12.2.2. The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0°C ~ 40°C Relatively humidity: ≤80%

12.2.3. The LCD modules should be stored in the room without acid, alkali and harmful gas.

12.3 Transportation Precautions

The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.